

Features

A perfect design, built especially for professional timber framing. The robust construction allows for continuous operation. Motor brushes are housed in solid brass guides, self disabling on end of life. All metal cast housing is used for cooling and to lend substance for solid positioning on timber, when used with guide stand. Very quiet transmission box. Sturdy mechanism for mounting chain tool, to prevent running out of square.



Tool is generally delivered with guide stand for square positioning on timbers. Precise vertical movement through oversized guide shafts. Gas spring assists return after plunge. End stop adjustment for depth of mortise.

Mortiser can be used without guide stand by use of attachable fence. Depth of cut: about 6.0". Chain and bar length of either choice: 1½" or 2.0". Cable length of 33 feet.

Please note: To allow for template scribing, our chains are undersized by a fraction to allow for clean-out of mortise with chisel after plunge cut. The 1½" chain is actually 37 mm wide instead of 38.2 mm. The 2.0" chain is 50 mm wide instead of 50.8 mm.

A perfect machine with plentiful accessories. For expansion into slotter, or specialty size and length of mortising bar are not only possible, but often ordered and delivered. I.E. 8" or even 12" depth of mortise bar/chain together with a taller guide stand.

Be it mortising, planing, sawing, routing: HEMA stands for quality of timber framing tools. For over 85 years HEMA has built a reputation for designing bandsaws for nearly any material used in manufacturing. The same solid, ergonomic design and reliability has gone into the timber framing tools. We guarantee it.

Specifications	
Rated input / Voltage	2.0 kW/230 V
Speed of drive gear	4250rpm
width of cut	28 mm
length of cut	35, 40, 50 mm, 1½"
Depth of plunge	100/150 mm / 4.0/6.0"
Weight, with guide stand	8.2kg/18lbs



Contact Information: TimberTools.com
11 Church Street
Brampton, ON L6Y 0J5

www.timbertools.com
Email: sales@timbertools.com
Phone: 416-675-2366
1-800-350-8176
Fax: 416-675-4242