

## Description

Land Ark is made only with natural, non-altered ingredients from sustainable resources, without chemical processing, bleaching or harmful additives. It is biologically degradable, non ozone depleting. Land Ark produces a natural, easily repaired finish on any woodwork, enhancing the patina and grain pattern on the species on which it is applied. Because it contains no drying agent of any kind, Land Ark may be left on the wood surfaces for extended times (from an hour to overnight) without gumming or hardening, thus greatly enhancing absorption into the wood. The finish keeps wicking deeper into the fibers, grain, and checks long after the surface is dry. Because it is not merely a surface finish, the resulting finish is highly resistant to scuffing and abrasion. It is easily repaired by simply rubbing in more finish with an abrasive pad.

## Application

Stir before using. Suitable with any applicator and application technique: thin-and-dry coating, surface flooding and buff-dry, wet sanding, french polishing, mechanical buffing. Avoid application in direct sunlight if at all possible.

## Liquid Finish

For interior, use as a primer to maintain dimensional stability, a base coat, or a complete one or two-coat finish on any wood. May be thickened with soft wax, if desired. Minimum coverage 500 sq/ft or board/foot per gallon.

## Soft Wax

Use as a superb end grain and joinery sealer (will NOT stain timbers), use on V-groove ceilings and paneling, cabinets doors and flooring. Excellent for periodic maintenance and cleaning of timber frames

## Liquid Finish and Soft Wax with aniline dye

Produces beautiful wood tones; a fool proof, one-step wiping stain and finish. Excellent color fastness due to the deep penetration of the finish. Dyes may be blended for additional colors. Coverage of soft wax 1000 sq/ ft per gallon

## Exterior finish

Mildewcide additive available for exterior use when needed. Avoid applying in direct sunlight. Allow sufficient weathering to "break" mill glaze from planing. Apply 2-3 wet on wet coats. Avoid application in the rain. Apply final 1-2 coats in 3-4 months. Clean and re-apply as needed over time.

## Composition: Contains no petroleum products, chemical additives, or metallic drying agents.

Tung oil: 100% pure with no additives; highest quality; dries harder and more durable than linseed oil alone. Both of the oils are drier-free and slightly heat treated or polymerized.

Linseed oil: Purified and refined by natural oxidation; dries as clear or clearer than tung oil, with none of the characteristic discoloration that is typical of hardware store varieties. No other finishing oil penetrates as deeply into wood.

Beeswax: Filtered, chemical and bleach-free cappings wax is only used; beeswax adds visual depth of grain, smoothness, and elastic durability to the finish; it also forms a skim coat that keeps the finish on the wood, slowing the evaporation of the solvent, and thus giving the oil more time for absorption.

D-Limonene: Food grade; this is the purest form of citrus turpenes (citrus extract), and it is extracted only from the cold-pressed oil of the orange peel; the only solvent used in Land Ark finishes.

Natural rosin: Gum rosin extracted from the sap of the pine tree and separated from the turpentine. This is the gum rosin found in heart pine, giving the wood its hardness and durability. No synthetic rosins are used.

Cypress oil is no longer available. We are now using a fungicide and UVA that both have safe environmental profiles. MSDS reports available on request.

**Contact Information:** [www.timbertools.com](http://www.timbertools.com)  
11 Church Street  
Brampton, ON L6Y 0J5

**Email:** [sales@timbertools.com](mailto:sales@timbertools.com)  
**Phone:** 416-675-2366  
1-800-350-8176  
**Fax:** 416-675-4242