

HEMA Beam PlanersFor the professional trade

Features

- German Engineering. Reliable operation. Motor with electronic control for soft start, constant speed, 3-4 second brake, and overload protection shown with light emitting diode (LED)
- · Handle position and large base assures solid tracking on start of planing and leaving your work piece
- Two-knife drum, reversible one-way blades, no adjustment required. Tri-metal with cobalt/molybdenum for long life, yet lower cost. Our knives are quadruple cross-ground and polished. Provides sharper edge, longer up-time, increases quality of planed wood and exits shavings more efficiently from the machine
- Robust, vibration free aluminum housing provides proper weight/cut ratio
- Full use of designated width through integrated, but retractable fence tracking roll
- Depth of cut adjustment in front on clearly marked scale. Can be adjusted during planing action
- · V-groove in center of base for easy bevel operation

Model ZBH 20

· Planing width: 205 mm (8 1/16")

· Max depth of cut: 3 mm, recommended: 2 mm

Power: 2000 Watt at 230 Volt No-load speed: 13500 rpm

· Cutting speed under power: 28 m/sec

Weight: 13.0 kg

Model ZBH 30

Weight balanced for easy handling

· Reduced noise through new poly-V-belt, considerably longer belt life.

Shavings exit to side of workpiece Planing width: 300 mm (11.81")

Max depth of cut: 3.5 mm, recommended: 2.5 mm

Power: 2100 Watt at 230 Volt no-load speed: 10300 rpm

Cutting speed under power: 28 m/sec

· Weight: 15.8 kg

Model ZBH 35

Solid performer. Enormous power. Super wide. Features are the same

as ZBH 30, but has heavier duty motor

· Planing width 350 mm (13 ³/₄")

· Max depth of cut: 2.5 mm, recommended: 2.0 mm

Power: 2500 Watt at 230 Volt no-load speed: 12000 rpm

Cutting speed under power: 28 m/sec

Weight 18 kg







Contact Information: TimberTools.com
11 Church Street
Brampton, ON L6Y 0J5

Email: <u>sales@TimberTools.com</u>
Phone: 1-800-350-8176
416-675-2366

Fax: 416-675-4242