

HEMA Notcher / Tenon cutter

Cutting of Birds mouths, Pockets

Features

This tool is designed for precision skew notches, lap joints, housings or creating birds mouth cuts or tenons. Most efficiently used for gang cutting of same measures across rafters and beams. Designed for tough jobs. Not many portable tools are as powerful as the ZF-215.



- A tool for high productivity and minimal effort. It removes large quantities of wood as deep as $3\frac{1}{2}$ " or as wide as $1\frac{3}{4}$ ".
- · Fence with integrated profile for tracking on guide rails. Hinged guards
- · Safety through electro-mechanical brake
- Two types of cutter heads for tenoning or notching
- Mark the center line of the cut across the rafters or beams positioned side by side.
 Angle and depth of cut can be accurately set for the cutter head. Now the cut can be made with precision, in one operation, across a whole series of beams or rafters.
- When you begin notching you will notice the quiet operation and vibration free running. This machine features a balanced weight and height. Note: the vertically positioned motor for providing balance.
- The ZF-215 is solidly built for uninterrupted work flow.





On notching the depth adjustment swings independently from scale



Kerf-cut of birds mouths



Clearly readable, permanently marked scale allows precise work

Specifications	
Rated input /Voltage /RPM	2800 W / 230 V / 3400
Cutting angle	0° - 60°
Notching cutter diameter Tenon cutter diameter	150 x 115 mm (6" x 4.75") 215 x 40 mm (10" x 1 ³ / ₄ ")
Maximum cutting depth	65 mm (2.55")
Weight, without tool bits	22.5 kg (48 lbs)

Contact Information: TimberTools.com

11 Church Street

Brampton, ON L6Y 0J5

Email: <u>sales@timbertools.com</u>
Phone: 1-800-350-8176

416-675-2366 Fax: 416-675-4242